



9554/7HN & 9558HP SERIES

115mm & 125mm Angle Grinders

9554HN 710W
9557HN 840W
9558HP 840W



Shaft lock system
for safe and easy replacement of abrasive wheel

Rotatable gear housing

Powerful motor

Small circumference barrel grip
for easy handling & operator comfort

O Rings

Dust-proof ball bearing

Gear section with increased reparability

Labyrinth construction

Paddle switch
For use in workplaces where safety is specified, especially the mining industry.



Model 9558HP

Slide switch
Suitable size and position for easy left or right hand operation.



Models 9554HN & 9557HN

MAKITA ADVANTAGE

- Rotatable gear housing can be positioned every 90° to suit most cutting and grinding operations.
- Powerful motor, with new spiral gears for less friction heat & noise, ensures steady and efficient masonry cutting.
- Labyrinth construction protects all ball bearings from dust and debris.
- Use of a woodruff key to assemble gear onto spindle allows for easier repairing of gear section.
- Dust-proof ball bearing on the spindle and the commutator end of the armature and a dust-proof washer is also installed on the spindle.
- O Rings placed in the following portions:
 - Joint between the gear housing and bearing box
 - Shaft lock pin installation hole.

SPECIFICATIONS:

	9554NB	9557HN	9558HP
Maximum Capacities:			
Depressed centre wheel	115mm	115mm	125mm
Abrasive disc	115mm	115mm	125mm
Diamond wheel	115mm	115mm	125mm
Continuous rating input	710W	840W	840W
No load speed	10 000 r/min	11 000 r/min	11 000r/min
Overall length	258mm	271mm	273mm
Net weight	1.8kg	2.0kg	2.1kg
Power supply cord	2.5m	2.5m	2.5m
Carbon brush	CB325	CB325	CB325

FEATURES:

Double insulation

STANDARD EQUIPMENT:

Depressed centre wheel, lock nut wrench & grip

OPTIONAL ACCESSORIES

Description	Part No.	Part No.	Part No.
Diamond blade, segmented	A-84109	A-84109	A-84115 or A-80438
Diamond blade, corrugated	A-84143	A-84113	
Diamond blade, waffle			B-02054
Inner flange 13-42 DIN45	224298-7	224298-7	224298-7
Lock nut 14-45	224543-0	224543-0	224543-0
Lock nut wrench 35 large 2 pin	782407-9	782407-9	782407-9
Rubber pad & nut	100	100	B-008060
Sanding lock nut 14 -48	224515-5	224515-5	224515-5
Special lock nut 14-45	192567-3	192567-3	192567-3
(Prevents lock-up)			

